



# Video sender with «multisource»



**Product number : VK50SSBE**

## Benefits

Many homes have multiple users of the Audio/Video system. Each one with their favourite movie, music, TV programme, or SAT channel. Often family disagreements start with the choice of Sunday night's entertainment. The Video Sender with «multisource» can help stop these family feuds.

The standard Video Sender transmits the source that is being used at that moment. This is perfect for when you want flexibility to watch a DVD in the bedroom or study, but both the main TV and the second TV are tuned to the same source. With «multisource» the Video Sender can transmit another source so that the second TV isn't watching the same programme as the main TV. And the source is selectable, remotely, with any remote.

The connection of Audio/Video equipment is quite complex. The SSB (Smart Scart Box) simplifies the installation of the Video Sender, making it easy for any consumer.

X10 Video Sender with Multisource is the first step towards wireless distribution of Audio/Video throughout your home.

The quality of transmission is excellent.

### COMPONENTS

- A/V Transmitter Unit
- A/V Receiver Unit
- Plug-in power supplies
- SMART scart box

### Transmitter :

- AV Input : Mini DIN,
- IR extender cable with 3 IR eyes

### Receiver :

- 1 cable plug with RCA-SCART
- 1 RCA/RCA cable

## Key Features

- Watch any A/V source (VCR, SAT, DVD...) on a second TV, even different from the main TV, with no cables or wires.
- Zap from one source to another, from the comfort of your second TV armchair, simply using your original remote control.
- New unobtrusive Video Sender design.
- Very easy connection, thanks to SMART SCART BOX.
- High quality broadband FM modulation.
- Full bandwidth HiFi stereo.

## Technical details

### BOTH UNITS :

- Four position 2.4 GHz channel selector switch
- ON / OFF switch

### SPECIFICATIONS

- Approvals:CE Mark,
- Radio : EN 300 200-1-3, I-ETS 300 440,
- EMC : EN 301 489-3,
- Electrical Safety : EN 61 558-2-6:1997  
EN 61 558-1 : 1997 + A1:1998

### Transmitter

- Power brick 230VAC/12V DC 200mA
- 1 Mini DIN for Audio/Video signal
- Modulation method: FM (Video & Audio)
- Video input : 1 v p-p (typ) / 75 ohms
- Audio input : 1 v p-p (typ) / 10 K Ohms
- 433.92MHz Antenna
- Operating range : 100 m open field
- Size : 35 x 95 x 90mm

### Scart Box

- AV input / output: 2 SCART and 1 Mini DIN

### Receiver

- Power brick 230V AC / 9 V DC 400mA
- 3 Phono sockets for audio left/right and video.
- Video output : 1 v p-p (typ) / 75 Ohms
- Audio output : 1 v p-p (typ) / 600 Ohms
- 433,92 MHz Antenna
- Size : 35 x 95 x 90mm